

Company Address	MONTERO FYE S.A., Retuerto s/n, 48903 Barakaldo, Vizcaya-España
Gasket Type	BELPA® CSA 90
Sealing element dimensions [mm]	92 x 49 x 2

L [mg/(s*m)]	Q <sub>min/L</sub> [MPa]	Minimum stress to seal Q <sub>min/L</sub> (at assembly), Q <sub>Smin/L</sub> (after off-loading) for p = 40 bar								
		Q <sub>Smin/L</sub> [MPa]								
		Q <sub>A</sub> = 20 MPa	Q <sub>A</sub> = 40 MPa	Q <sub>A</sub> = 60 MPa	Q <sub>A</sub> = 80 MPa	Q <sub>A</sub> = 100 MPa	Q <sub>A</sub> = 120 MPa	Q <sub>A</sub> = 140 MPa	Q <sub>A</sub> = 160 MPa	
10 <sup>0</sup>	10	10	10	10	10	10			10	
10 <sup>-1</sup>	19	16	10	10	10	10			10	
10 <sup>-2</sup>	27		10	10	10	10			10	
10 <sup>-3</sup>	35		13	10	10	10			10	
10 <sup>-4</sup>	47			15	10	10			10	
10 <sup>-5</sup>	77				69	40			43	
10 <sup>-6</sup>										
10 <sup>-7</sup>										
10 <sup>-8</sup>										



